

## Technical details: “Jungbrunnen 66-12”

- 9 steps reverse osmosis
  - 1. prefiltration: 5 micron
  - 2. active coal filtration
  - 3. prefiltration: 1 micron
  - 4.-7. membrane: **0,0001 micron**
  - 8. HE-module
  - 9. Aqua-Lith-Crystal Energy
- connection (electr.) 230 V – 50 Hz
- tap: high-grade steel designer tap
- water tank: internal: approx. 12 l
- measures (water tank): h 385mm x w 280mm x d 280mm  
air pressure: 0,4 bar – 3,2 bar
- “CE” certificate
- measures: h 421mm x w 295mm x d 430mm
- weight (without water): approx. 19 Kg
- drinking water production: approx. up to **2.500** l / 24 h.  
approx. up to 1,7 l / min.
- option to connect: external drinking fountain
- connection: 1 x ¾”
- cold water connection: “3/8” plastic hose
- kind of connection: “Quick” – connection
- outlet clamp fitting set: 40 – 50 mm
- incoming water max. TDS < 2.000 ppm salt and < 0,2 mg/l.  
iron
- incoming water pH-level: 6,5 – 9,5
- incoming water pressure: min. 1,5 bar
- incoming water temp.: approx. 5°C. – approx. 40,5°C.\*
- minimum pressure: approx. 1.5 bar
- maximum working pressure: approx. 4,5 bar\*
- warranty: 1 year

\* could damage the warranty

Sabreen Water Technology L.L.C – Dubai (U.A.E.) +971 529 355 929