## Technical details: "Jungbrunnen 66:00 Ultimate"

<ul><li>no use of bottles</li><li>costs saving up to 75%</li><li>very simple operation</li></ul>	
<ul> <li>7 steps reverse osmosis</li> <li>1. prefiltration:</li> <li>2. active coal filtration</li> <li>3. prefiltration:</li> <li>4 + 5. membrane: 50 GPD</li> <li>6. Aqua-Lith-Crystal-Energy</li> <li>7. HE-module</li> </ul>	20 μ 5 μ <b>0,0001 μ</b>
<ul> <li>permeate pump (without electricity)</li> <li>tap:</li> <li>water tank:</li> </ul>	for production of <b>11</b> purest water only needs 2 l normal water (other systems need up to <b>7 l</b> ) full high-grade surgery stainless steel designer tap 7,5 l (4,0 bar water pressure)
<ul> <li>german TÜV tested</li> <li>"CE" certifícate</li> </ul>	air pressure: 0,35 bar – 0,5 bar inside and outside the whole system system with booster pump
<ul><li>measures:</li><li>weight:</li><li>drinking water production:</li></ul>	h 410mm x w 310mm x d 463mm 12,5 Kg approx. up to <b>370</b> l/day (with approx. 4,0 bar water pressure)
- filter change:	filter nr. 1 every 6 monthes filter nr. 2, 3, 6 every year module 7 every 3 years
<ul> <li>connection:</li> <li>cold water connection:</li> <li>kind of connection:</li> <li>outlet clamp fitting set:</li> </ul>	1 x <sup>3</sup> / <sub>4</sub> " <sup>1</sup> / <sub>4</sub> " plastic hose "Quick" – connection 40 – 50 mm
<ul> <li>incoming water max. TDS</li> <li>incoming water pH-level:</li> <li>incoming water pressure:</li> <li>incoming water temp.:</li> <li>minimum pressure:</li> <li>maximum working pressure:</li> <li>warranty:</li> </ul>	< 2.000 ppm salt and < 0,2 mg/l iron 6,5 – 9,5 approx. 3,0 bar – 7,0 bar approx. 4,4°C. – approx. 40,5°C.* approx. 3,0 bar approx. 7,0 bar* <b>30 years (in conjunction with</b> <b>current BW filter change)</b> <u>only private use! in Germany</u>
• could damage the warranty	om, prive user in Germuny