

### Technical details Jungbrunnen 66-11

9 steps reverse osmosis	1. prefiltration 5 $\mu$ 2. active coal filtration 3. prefiltration 1 $\mu$ 4. – 7. membrane <b>0,0001 <math>\mu</math></b> 8. aqua-lith crystal energy module 9. HE – module
clean water / outlet water ratio	1 to 1,2
tap	100% surgical full stainless steel designer tap
water storage tank (to connect a washing machine or /and dishwasher)	stainless steel, internal: approx. 12 litre air pressure: 0,35 – 0,5 bar h 385 mm x w 280 mm x d 280 mm
German TÜV tested ( <b>ID.N° 24643</b> ) DIN 1988 CE certified	inside and outside the whole system requirements for use drinking water
measures:	h 421 mm x w 295 mm x d 430 mm
weight:	approx. 19 Kg / water storage tank approx. 2,8 Kg
drinking water production:	1,7 litre / min.
water connection:	1 x $\frac{3}{4}$ "
cold water connection:	$\frac{3}{8}$ " plastic hose
kind of connection	"Quick" connection
outlet clamp fitting set:	40 – 50 mm
incoming water max. TDS	< 2.000 ppm salt / < 0,2 mg iron
incoming water pH level	6,5 – 9,5
incoming water temp.:	approx. 5° C – approx. 40,5 C°
min. system pressure	1,5 bar
max. system pressure	4,5 bar
power supply	230 V – 50 Hz
power consumption at operation	170 W
power consumption at standby	< 1 W
disinfection	every 6 months
filter change:	filter nr. 1 every 6 months – filter nr. 2,3,8 yearly, filter nr. 9 every 3 years
warranty:	private use: 30 years (in conjunction with original filter change) commercial: 1 year

Sabreen Water Technology L.L.C – Dubai (U.A.E.) +971 529 355 929