

**Technical details mobile system  
WATERSTATION SPORT**

6 steps reverse osmosis	<ol style="list-style-type: none"><li>1. prefiltration 5 <math>\mu</math></li><li>2. active coal filtration</li><li>3. prefiltration 1 <math>\mu</math></li><li>4. membrane <b>0,0001 <math>\mu</math></b></li><li>5. aqua-lith crystal energy module</li><li>6. HE – module</li></ol>
booster pump power supply	75 W 230 V – 50 Hz
DIN 1988 CE certified	requirements for use drinking water
measures:	h 410 mm x w 340 mm x d 140 mm
weight:	approx. 11,7 Kg
drinking water production:	approx. 280 litre/day if water pressure is 6,5 bar
water connection:	1 x $\frac{3}{4}$ " M22/M24
cold water connection:	$\frac{1}{4}$ " plastic hose
kind of connection	"Quick" connection
outlet clamp fitting set:	40 – 50 mm
incoming water max. TDS	< 2.000 ppm salt / < 0,2 mg iron
incoming water pH level	6,5 – 9,5
incoming water pressure:	1,5 – max. 7.0 bar
incoming water temp.:	approx. 4,4° C – approx. 40,5 C°
disinfection	every 6 months
filter change:	filter nr. 1, 2, 3, 5 every 6 months filter nr. 6 every 2 years
warranty:	1 year