

Technical details Jungbrunnen 25-00

5 steps reverse osmosis	<ol style="list-style-type: none">1. prefiltration 5μ2. activated coal filtration3. membrane 0,0001 μ4. aqua lith crystal energy module5. HE module
water storage tank	8 litre normal – 4 litre cold – 2 litre hot
hot water temp.	85° C. – 100° C.
cold water temp.	4° C. - 12° C.
power	warm up: 700 W / cooling: 100 W
cool system	without Freon gas
power supply	240 V – 50 Hz
CE certified	
DIN 1988	requirements for use drinking water
CE certified	
measures:	h 1050 mm x w 400 mm x d 320 mm
weight:	approx. 17 Kg
drinking water production:	approx. up to 200 litre / day (8,3 litre/h) (approx. 6,5 bar water pressure)
water connection:	1 x $\frac{3}{4}$ "
cold water connection:	$\frac{3}{4}$ " plastic hose
kind of connection	"Quick" connection
outlet clamp fitting set:	40 – 50 mm
incoming water max. TDS	< 2.000 ppm salt / < 0,2 mg iron
incoming water pH level	6,5 – 9,5
incoming water temp.	approx. 4,4° C – approx. 40,5 C°
incoming water pressure	approx. 2,8 - 6 bar
incoming water pressure	min. 1,5 bar (system with booster pump)
disinfection	every 6 months
filter change	filter nr. 1 every 6 months filter nr. 2, 4 every 12 months filter nr. 5 every 2 years
warranty	1 year